

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version 2.0 Revision Date: 07/31/2018 SDS Number: 400001000047 Date of last issue: 05/24/2018
Date of first issue: 11/10/2016

SECTION 1. IDENTIFICATION

Product name : LIQUID DIAMONDS RESIN - A

Manufacturer or supplier's details

Company name of supplier : The Epoxy Resin Store
Address : 18510 Pasadena Street
United States of America (USA)

Telephone : (800) 897-7531

E-mail address of person responsible for the SDS : support@theepoxyresinstore.com

Emergency telephone number : (800) 897-7531

Recommended use of the chemical and restrictions on use

Recommended use : Epoxy constituents

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with 29 CFR 1910.1200

Skin irritation : Category 2
Eye irritation : Category 2A
Skin sensitisation : Category 1
Short-term (acute) aquatic hazard : Category 2
Chronic aquatic toxicity : Category 2

GHS label elements

Hazard pictograms :

Signal word : Warning

Hazard statements : H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version 2.0 Revision Date: 07/31/2018 SDS Number: 400001000047 Date of last issue: 05/24/2018
Date of first issue: 11/10/2016

P264 Wash skin thoroughly after handling.
P272 Contaminated work clothing must not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves/ eye protection/ face protection.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P391 Collect spillage.
Storage:
Not available
Disposal:
P501 Dispose of contents/container to an approved facility in accordance with local, regional, national and international regulations.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Substance

Hazardous components

Chemical name	CAS-No.	Concentration (% w/w)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane	1675-54-3	90 - 100

The specific chemical identity and/or exact percentage (concentration) of composition may be withheld as a trade secret.

Both 25068-38-6 and 1675-54-3 can be used to describe the epoxy resin which is produced through the reaction of Bisphenol A and Epichlorhydrin

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Treat symptomatically.
Get medical attention if symptoms occur.

If inhaled : If inhaled, remove to fresh air.
Get medical attention if symptoms occur.

In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version	Revision Date:	SDS Number:	Date of last issue: 05/24/2018
2.0	07/31/2018	400001000047	Date of first issue: 11/10/2016

- If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : None known.
- Notes to physician : Treat symptomatically.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : No hazardous combustion products are known
- Carbon oxides
Halogenated compounds
- Specific extinguishing methods : No data is available on the product itself.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Prevent product from entering drains.

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version	Revision Date:	SDS Number:	Date of last issue: 05/24/2018
2.0	07/31/2018	400001000047	Date of first issue: 11/10/2016

Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep in properly labelled containers.

Materials to avoid : Strong acids
Strong bases
Strong oxidizing agents

Recommended storage temperature : 36 - 104 °F / 2 - 40 °C

Further information on storage stability : No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version	Revision Date:	SDS Number:	Date of last issue: 05/24/2018
2.0	07/31/2018	400001000047	Date of first issue: 11/10/2016

supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material : butyl-rubber
Break through time : > 8 h

Material : Ethyl Vinyl Alcohol Laminate (EVAL)
Break through time : > 8 h

Material : Nitrile rubber
Break through time : 10 - 480 min

Material : Neoprene
Break through time : 10 - 480 min

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles
Wear face-shield and protective suit for abnormal processing problems.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : slight

Odour Threshold : No data is available on the product itself.

pH : ca. 7 (68 °F / 20 °C)
Concentration: 500 g/l

Freezing point : No data is available on the product itself.

Melting point : No data is available on the product itself.

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version 2.0 Revision Date: 07/31/2018 SDS Number: 400001000047 Date of last issue: 05/24/2018
Date of first issue: 11/10/2016

Boiling point : > 392 °F / > 200 °C

Flash point : > 392 °F / > 200 °C
Method: Pensky-Martens closed cup

Evaporation rate : No data is available on the product itself.

Flammability (solid, gas) : No data is available on the product itself.

Flammability (liquids) : No data is available on the product itself.

Upper explosion limit / Upper flammability limit : No data is available on the product itself.

Lower explosion limit / Lower flammability limit : No data is available on the product itself.

Vapour pressure : < 0.0001 hPa (77 °F / 25 °C)

Relative vapour density : No data is available on the product itself.

Relative density : 1.15 - 1.17 (77 °F / 25 °C)

Density : 1.17 - 1.2 g/cm³ (77 °F / 25 °C)

Solubility(ies)

 Water solubility : practically insoluble (68 °F / 20 °C)

 Solubility in other solvents : No data is available on the product itself.

Partition coefficient: n-octanol/water : log Pow: 3.8 (77 °F / 25 °C)

Auto-ignition temperature : does not ignite

Decomposition temperature : > 392 °F / > 200 °C

Self-Accelerating decomposition temperature (SADT) : No data is available on the product itself.

Viscosity

 Viscosity, dynamic : 10,000 - 12,000 mPa.s (77 °F / 25 °C)

Explosive properties : No data is available on the product itself.

Oxidizing properties : No data is available on the product itself.

Particle size : No data is available on the product itself.

SECTION 10. STABILITY AND REACTIVITY

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version 2.0 Revision Date: 07/31/2018 SDS Number: 400001000047 Date of last issue: 05/24/2018
Date of first issue: 11/10/2016

Reactivity : No dangerous reaction known under conditions of normal use.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : No hazards to be specially mentioned.
Conditions to avoid : None known.

Incompatible materials : Strong acids
Strong bases
Strong oxidizing agents

Hazardous decomposition products : carbon dioxide
carbon monoxide
Halogenated compounds

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : No data is available on the product itself.

Acute toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Acute oral toxicity : LD50 (Rat, female): > 2,000 mg/kg
Components : Method: OECD Test Guideline 420
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Acute dermal toxicity : LD50 (Rat, male and female): > 2,000 mg/kg
Method: OECD Test Guideline 402
Assessment: The substance or mixture has no acute dermal toxicity

Acute toxicity (other routes of administration) : No data available

Skin corrosion/irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Species: Rabbit
Assessment: Mild skin irritant
Method: OECD Test Guideline 404
Result: Irritating to skin.

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version 2.0 Revision Date: 07/31/2018 SDS Number: 400001000047 Date of last issue: 05/24/2018
Date of first issue: 11/10/2016

Serious eye damage/eye irritation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Species: Rabbit
Result: Irritating to eyes.
Assessment: Mild eye irritant
Method: OECD Test Guideline 405

Respiratory or skin sensitisation

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Exposure routes: Skin
Species: Mouse
Assessment: May cause sensitisation by skin contact.
Method: OECD Test Guideline 429
Result: Causes sensitisation.

Assessment: No data available

Germ cell mutagenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Genotoxicity in vitro : Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: positive

Concentration: 0 - 5000 ug/plate
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: positive

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Genotoxicity in vivo : Cell type: Germ
Application Route: Oral
Method: OECD Test Guideline 478
Result: negative

Cell type: Somatic
Application Route: Oral
Dose: 0 - 5000 mg/kg
Method: OPPTS 870.5395
Result: negative

Carcinogenicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Species: Rat, male and female
Application Route: Oral
Exposure time: 24 month(s)
Dose: 15 mg/kg

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version	Revision Date:	SDS Number:	Date of last issue: 05/24/2018
2.0	07/31/2018	400001000047	Date of first issue: 11/10/2016

Frequency of Treatment: 7 days/week
Method: OECD Test Guideline 453
Result: negative

Species: Mouse, male
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 0.1 mg/kg
Frequency of Treatment: 3 days/week
Method: OECD Test Guideline 453
Result: negative

Species: Rat, female
Application Route: Dermal
Exposure time: 24 month(s)
Dose: 1 mg/kg
Frequency of Treatment: 5 days/week
Method: OECD Test Guideline 453
Result: negative

Carcinogenicity - Assessment : No data available

IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on fertility : Test Type: Two-generation study
Species: Rat, male and female
Application Route: Oral
Dose: >750 milligram per kilogram
General Toxicity - Parent: No-observed-effect level: 540 mg/kg body weight
General Toxicity F1: No-observed-effect level: 540 mg/kg body weight
Symptoms: No adverse effects
Method: OECD Test Guideline 416
Result: No effects on fertility and early embryonic development were detected.

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version Revision Date: SDS Number: Date of last issue: 05/24/2018
2.0 07/31/2018 400001000047 Date of first issue: 11/10/2016

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Effects on foetal development : Species: Rabbit, female
Application Route: Dermal
General Toxicity Maternal: No observed adverse effect level:
30 mg/kg body weight
Method: Other guidelines
Result: No teratogenic effects

Species: Rabbit, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
60 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Species: Rat, female
Application Route: Oral
General Toxicity Maternal: No observed adverse effect level:
180 mg/kg body weight
Method: OECD Test Guideline 414
Result: No teratogenic effects

Reproductive toxicity - Assessment : No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Repeated dose toxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Species: Rat, male and female
NOAEL: 50 mg/kg
Application Route: Ingestion
Exposure time: 14 Weeks
Number of exposures: 7 d
Method: Subchronic toxicity

Species: Rat, male and female
NOEL: 10 mg/kg
Application Route: Skin contact
Exposure time: 13 Weeks
Number of exposures: 5 d
Method: Subchronic toxicity

Species: Mouse, male
NOAEL: 100 mg/kg
Application Route: Skin contact
Exposure time: 13 Weeks

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version 2.0	Revision Date: 07/31/2018	SDS Number: 400001000047	Date of last issue: 05/24/2018 Date of first issue: 11/10/2016
----------------	------------------------------	-----------------------------	---

Number of exposures: 3 d
Method: Subchronic toxicity

Repeated dose toxicity - Assessment : No data available

Aspiration toxicity

No data available

Experience with human exposure

General Information: No data available

Inhalation: No data available

Skin contact: No data available

Eye contact: No data available

Ingestion: No data available

Toxicology, Metabolism, Distribution

No data available

Neurological effects

No data available

Further information

Ingestion: No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.5 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: Fresh water
Method: OECD Test Guideline 203

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version 2.0 Revision Date: 07/31/2018 SDS Number: 400001000047 Date of last issue: 05/24/2018
Date of first issue: 11/10/2016

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2.7 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: Fresh water

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Toxicity to algae : EC50 (Selenastrum capricornutum (green algae)): 9.4 mg/l
Exposure time: 72 h
Test Type: static test
Test substance: Fresh water
Method: EPA-660/3-75-009

M-Factor (Acute aquatic toxicity) : No data available

Toxicity to fish (Chronic toxicity) : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.3 mg/l
Exposure time: 21 d
Test Type: semi-static test
Test substance: Fresh water
Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity) : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:
Toxicity to microorganisms : IC50 (activated sludge): > 100 mg/l
Exposure time: 3 h
Test Type: static test
Test substance: Fresh water

Toxicity to soil dwelling organisms : No data available

Plant toxicity : No data available

Sediment toxicity : No data available

Toxicity to terrestrial organisms : No data available

Ecotoxicology Assessment
Acute aquatic toxicity : No data available

Chronic aquatic toxicity : No data available

Toxicity Data on Soil : No data available

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version Revision Date: SDS Number: Date of last issue: 05/24/2018
2.0 07/31/2018 400001000047 Date of first issue: 11/10/2016

Other organisms relevant to the environment : No data available

Persistence and degradability

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Biodegradability : Inoculum: Sewage (STP effluent)
Concentration: 20 mg/l
Result: Not readily biodegradable.
Biodegradation: 5 %
Exposure time: 28 d
Method: OECD Test Guideline 301F

Biochemical Oxygen Demand (BOD) : No data available

Chemical Oxygen Demand (COD) : No data available

BOD/COD : No data available

ThOD : No data available

BOD/ThOD : No data available

Dissolved organic carbon (DOC) : No data available

Physico-chemical removability : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Stability in water : Degradation half life(DT50): 4.83 d (77 °F / 25 °C) pH: 4
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life(DT50): 7.1 d (77 °F / 25 °C) pH: 9
Method: OECD Test Guideline 111
Remarks: Fresh water

Degradation half life(DT50): 3.58 d (77 °F / 25 °C) pH: 7
Method: OECD Test Guideline 111
Remarks: Fresh water

Photodegradation : No data available

Impact on Sewage Treatment : No data available

Bioaccumulative potential

Components:

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version 2.0 Revision Date: 07/31/2018 SDS Number: 400001000047 Date of last issue: 05/24/2018
Date of first issue: 11/10/2016

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Bioaccumulation : Bioconcentration factor (BCF): 31
Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water - Product : log Pow: 3.8 (77 °F / 25 °C)

Mobility in soil

Mobility : No data available

Components:

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane:

Distribution among environmental compartments : Koc: 445

Stability in soil : No data available

Other adverse effects

Environmental fate and pathways : No data available

Results of PBT and vPvB assessment : No data available

Endocrine disrupting potential : No data available

Adsorbed organic bound halogens (AOX) : No data available

Hazardous to the ozone layer

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82
Protection of Stratospheric Ozone - CAA Section 602 Class I Substances
Remarks: This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information - Product : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

Global warming potential (GWP) : No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version	Revision Date:	SDS Number:	Date of last issue: 05/24/2018
2.0	07/31/2018	400001000047	Date of first issue: 11/10/2016

- Waste from residues : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.
Dispose of as hazardous waste in compliance with local and national regulations.
Dispose of contents/ container to an approved waste disposal plant.
- Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International Regulations

IATA

- UN/ID No. : UN 3082
Proper shipping name : Environmentally hazardous substance, liquid, n.o.s.
(BISPHENOL A EPOXY RESIN)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IMDG

- UN number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.
(BISPHENOL A EPOXY RESIN)
Class : 9
Packing group : III
Labels : 9
EmS Code : F-A, S-F
Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

DOT Classification

- UN/ID/NA number : UN 3082
Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID,
N.O.S.

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version 2.0 Revision Date: 07/31/2018 SDS Number: 400001000047 Date of last issue: 05/24/2018
Date of first issue: 11/10/2016

(BISPHENOL A EPOXY RESIN)
Class : 9
Packing group : III
Labels : CLASS 9
ERG Code : 171
Marine pollutant : yes(BISPHENOL A EPOXY RESIN)

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
1-chloro-2,3-epoxypropane	106-89-8	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Skin corrosion or irritation
Serious eye damage or eye irritation
Respiratory or skin sensitisation

SARA 313 : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

California Prop. 65

WARNING: This product can expose you to chemicals including 1-chloro-2,3-epoxypropane, which is/are known to the State of California to cause cancer, and 1-chloro-2,3-epoxypropane, 4,4'-isopropylidenediphenol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

4,4'-isopropylidenediphenol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

CH INV : On the inventory, or in compliance with the inventory
DSL : All components of this product are on the Canadian DSL
AICS : On the inventory, or in compliance with the inventory
NZIoC : On the inventory, or in compliance with the inventory
ENCS : On the inventory, or in compliance with the inventory
KECI : On the inventory, or in compliance with the inventory
PICCS : On the inventory, or in compliance with the inventory
IECSC : On the inventory, or in compliance with the inventory
TCSI : On the inventory, or in compliance with the inventory
TSCA : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version 2.0 Revision Date: 07/31/2018 SDS Number: 400001000047 Date of last issue: 05/24/2018
Date of first issue: 11/10/2016

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

TSCA - 5(a) Significant New Use Rule List of Chemicals

No substances are subject to a Significant New Use Rule.


US. Toxic Substances Control Act (TSCA) Section 12(b) Export Notification (40 CFR 707, Subpt D)

No substances are subject to TSCA 12(b) export notification requirements.

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



HMIS® IV:

HEALTH	2
FLAMMABILITY	1
PHYSICAL HAZARD	0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Revision Date : 07/31/2018

The information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and

SAFETY DATA SHEET

LIQUID DIAMONDS RESIN - A

Version	Revision Date:	SDS Number:	Date of last issue: 05/24/2018
2.0	07/31/2018	400001000047	Date of first issue: 11/10/2016

behaviour should be determined by the user and made known to handlers, processors and end users.

The trademarks above are the property of Huntsman Corporation or an affiliate thereof.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE.